



adesivi

TECHNICAL DATA SHEET



Review 001, 11/2022

Page 1 of 1

PRODUCT

REMOVER COMPOUND POLISH (C7146)

CHARACTERISTICS

REMOVER COMPOUND POLISH is a stabilized emulsion of micro-oxides that ensure high cutting power and performance. It is very concentrated, thus only a small amount should be used. It is recommended to remove quickly and easily scratches from clearcoats, paintwork and gelcoat imperfections, deep scratches and oxidation from metal surfaces. It is very easy to apply, water-based formulated and do not generate stains or dust. In one step it is possible to reach a gloss mirror, but optimal results, it is advisable to complete the full cycle.

TECHNICAL DATA

Specific weight	1180 ± 20 g/l	(MI 001)
Color	White	
pH	8	(MI 022)
Cut / Gloss	9 / 4 I step on a scale of 1 to 12 with a hard foam (1010/B)	
	6 / 6 II step on a scale of 1 to 12 with a medium foam (1010/A)	

STORAGE

Keep the container well closed and stored in a cool (temperature below 25°C) and ventilated environment for a maximum period of 12 months from the date of production marked on the tin. Avoid direct sun exposure and protect from freezing.

SAFETY

During application and drying time ventilate the room. We recommend the use of appropriate PPE during application. Before starting work, read safety instructions.

APPLICATION

- Make sure the surfaces to be treated are clean and do not apply in direct sunlight. Shake well before use
- Apply a small amount of product directly onto the surface to be treated or on the foam and spread it
- Wait 10-20 seconds, then buff using a random orbital polisher at 1500 rpm, applying medium pressure, first with a clean hard foam (1010/B) and then with a medium foam by reapplying the product. (1010/A) Good results can be obtained without using a polisher machine too, but in longer working times.
- On soft or sensitive paint, or where heat buildup may be a problem, the addition of water mist to avoid any friction burn, particularly with new pads, is recommended, but avoid excessive water.
- For an extra gloss enhancement, REMOVER COMPOUND POLISH should be followed with the FINISHING POLISH with a soft foam (1010/N) and then the NANO ULTRAPOLISHING WAX with a soft polishing cloth (1011/G or better 1011/GY)

ILPA ADESIVI SRL

Via Ferorelli, 4 – Zona Industriale – 70123 BARI – Italy – Tel. 0805383837 - Fax +390805377807 - E-mail: ilpasrl@ilpa.it
<http://www.ilpaadesivi.com> – Cap. Soc. € 218.400,00 i.v. – R.E.A. n. 152397 – Cod. Fisc. e P. IVA n. IT 00465900728 – Reg. imp. Bari n. 6525