

**L7111 - GEL COAT ORTO A PENNELLO**

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: L7111
Product name: GEL COAT ORTO A PENNELLO

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Putty to repair, Professional use only.

Uses advised against: no one in particular

Identified Uses	Industrial	Professional	Consumer
gelcoat	SU: 10, 12, 17. ERC: 2, 6d. PROC: 1, 10, 13, 14, 15, 3, 4, 5, 7, 8a, 8b, 9. AC: 13. PC: 32, 9a.	SU: 10, 12, 17. ERC: 6c. PROC: 10, 11, 3, 4, 5, 8a. AC: 13. PC: 32, 9a.	-

1.3. Details of the supplier of the safety data sheet

Name: ILPA ADESIVI SRL
Full address: Via Ferorelli, 4
District and Country: 70132 BARI (BARI)
ITALIA
Tel. + 39 0805383837
Fax + 39 0805377807

e-mail address of the competent person
responsible for the Safety Data Sheet: laboratorio@ilpa.it

1.4. Emergency telephone number

For urgent inquiries refer to: + 39 0808974667 (Technical support - 8,00 - 17,00 - LUN-VEN; MON-FRI)(Italian time zone)
Safety Executive (HSE) Chemicals Regulation Directorate 5S.1 Redgrave Court, Merton Road, Bootle, Merseyside. L20 7HS.
Phone: +44 151 9513317

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

**L7111 - LEVANTE - STUCCO GEL COAT**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H226	Flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.

Precautionary statements:

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust / fume / gas / mist / vapours / spray.
P280	Wear protective gloves / eye protection / face protection.
P308+P313	IF exposed or concerned: Get medical advice / attention.
P370+P378	In case of fire: use carbon dioxide, foam, chemical powder to extinguish.

Contains: STYRENE
 COBALT BIS 2-ETHYL HEXANOATE

Product not intended for uses provided for by Dir. 2004/42/CE.

**L7111 - LEVANTE - STUCCO GEL COAT****2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
STYRENE		
CAS 100-42-5	$22.5 \leq x < 24$	Flam. Liq. 3 H226, Repr. 2 H361d, Acute Tox. 4 H332, STOT RE 1 H372, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: D
EC 202-851-5		
INDEX 601-026-00-0		
Reg. no. 01-2119457861-32		
COBALT BIS 2-ETHYL HEXANOATE		
CAS 136-52-7	$0.1 \leq x < 0.15$	Repr. 2 H361f, Eye Irrit. 2 H319, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 3 H412
EC 205-250-6		
INDEX -		
Reg. no. 01-2119524678-29		
1-METHOXY-2-PROPANOL		
CAS 107-98-2	$0 \leq x < 0.05$	Flam. Liq. 3 H226, STOT SE 3 H336
EC 203-539-1		
INDEX 603-064-00-3		
Reg. no. 01-2119457435-35		
METHYL ETHYL KETONE		
CAS 78-93-3	$0 \leq x < 0.05$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 201-159-0		
INDEX 606-002-00-3		
Reg. no. 01-2119457290-43		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

**L7111 - LEVANTE - STUCCO GEL COAT**

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

PROTECTIVE MEASURES FOR THE FIRST RESCUE WORKERS: for PPE (personal protection equipment) required for first aid refer to section 8.2 of this safety data sheet.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

**L7111 - LEVANTE - STUCCO GEL COAT**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

No use other than specified in Section 1.2 of this safety data sheet.

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
HRV	Hrvatska	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/18)
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

STYRENE



L7111 - LEVANTE - STUCCO GEL COAT

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
AGW	DEU	86	20	172	40	
AGW	DEU	86	20	172	40	
AGW	DEU	86	20	172	40	
MAK	DEU	86	20	172	40	
MAK	DEU	86	20	172	40	
MAK	DEU	86	20	172	40	
VLA	ESP	86	20	172	40	
VLA	ESP	86	20	172	40	
VLEP	FRA	100	23.3	200	46.6	
WEL	GBR	430	100	1080	250	
TLV	GRC	425	100	1050	250	
GVI/KGVI	HRV	430	100	1080	250	SKIN
TGG	NLD	107				
TLV-ACGIH		85	20	170	40	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0.028	mg/l
Normal value in marine water	0.014	mg/l
Normal value for fresh water sediment	0.614	mg/kg/d
Normal value for marine water sediment	0.0614	mg/kg/d
Normal value for water, intermittent release	0.04	mg/l
Normal value of STP microorganisms	5	mg/l
Normal value for the terrestrial compartment	0.2	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	2,1 mg/kg bw/d				
Inhalation	182,75 mg/m ³	174,25 mg/m ³	VND	10,2 mg/m ³	306 mg/m ³	289 mg/m ³	VND	85 mg/m ³
Skin			VND	343 mg/kg bw/d			VND	406 mg/kg bw/d

COBALT BIS 2-ETHYL HEXANOATE**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0.0006	mg/l
Normal value in marine water	0.00236	mg/l
Normal value for fresh water sediment	9.5	mg/kg/d
Normal value for marine water sediment	9.5	mg/kg/d
Normal value of STP microorganisms	0.37	mg/l
Normal value for the terrestrial compartment	10.9	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers	Effects on workers
--	----------------------	--------------------

**ILPA ADESIVI SRL**

Revision nr. 1

Dated 23/06/2020

First compilation

Printed on 23/06/2020

Page n. 7/20

L7111 - LEVANTE - STUCCO GEL COAT

Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	NPI	VND	VND	0,0558 mg/kg bw/d				
Inhalation	NPI	NPI	0,037 mg/m3	NPI	NPI	NPI	0,235 mg/m3	VND
Skin	VND	NPI	VND	NPI	VND	NPI	VND	NPI

METHYL ETHYL KETONE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	600	200	600	200	SKIN
MAK	DEU	600	200	600	200	SKIN
VLA	ESP	600	200	900	300	
VLEP	FRA	600	200	900	300	SKIN
WEL	GBR	600	200	899	300	SKIN
TLV	GRC	600	200	900	300	
GVI/KGVI	HRV	600	200	900	300	
VLEP	ITA	600	200	900	300	
TGG	NLD	590		500		SKIN
VLE	PRT	600	200	900	300	
OEL	EU	600	200	900	300	
TLV-ACGIH		590	200	885	300	

Predicted no-effect concentration - PNEC

Normal value in fresh water	55.8	mg/l
Normal value in marine water	55.8	mg/l
Normal value for fresh water sediment	284.74	mg/kg/d
Normal value for marine water sediment	284.74	mg/kg/d
Normal value for water, intermittent release	55.8	mg/l
Normal value of STP microorganisms	709	mg/l
Normal value for the food chain (secondary poisoning)	1000	mg/kg
Normal value for the terrestrial compartment	22.5	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	31 mg/kg bw/d				
Inhalation			VND	106 mg/m3			VND	600 mg/m3
Skin			VND	412 mg/kg bw/d			VND	1161 mg/kg bw/d

1-METHOXY-2-PROPANOL**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	370	100	740	200	
MAK	DEU	370	100	740	200	



L7111 - LEVANTE - STUCCO GEL COAT

VLA	ESP	375	100	568	150	SKIN
VLEP	FRA	188	50	375	10	SKIN
WEL	GBR	375	100	560	150	SKIN
TLV	GRC	360	100	1080	300	
GVI/KGVI	HRV	375	100	568	150	
VLEP	ITA	375	100	568	150	SKIN
TGG	NLD	375		563		SKIN
VLE	PRT	375	100	568	150	
OEL	EU	375	100	568	150	SKIN
TLV-ACGIH		184	50	368	100	

Predicted no-effect concentration - PNEC

Normal value in fresh water	10	mg/l
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	52.3	mg/kg/d
Normal value for marine water sediment	5.2	mg/kg/d
Normal value for water, intermittent release	100	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	4.59	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic systemic	Effects on workers			
	Acute local	Acute systemic	Chronic local		Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	NPI	VND	33 mg/kg bw/d				
Inhalation	NPI	NPI	NPI	43,9 mg/m3	553,5 mg/m3	553,5 mg/m3	NPI	369 mg/m3
Skin	NPI	NPI	NPI	78 mg/kg bw/d	NPI	NPI	NPI	183 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

**L7111 - LEVANTE - STUCCO GEL COAT**

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	paste
Colour	white
Odour	aromatic
Odour threshold	0,32 ppm (STYRENE: <i>Journal of Applied Toxicology</i> , 3(6):272-290. 1983.)
pH	Not applicable.
Melting point / freezing point	-30,7 °C (STYRENE)
Initial boiling point	> 35 °C.
Boiling range	Not available.
Flash point	23 ≤ T ≤ 60 °C
Evaporation rate	12,4 (di-ethylether = 1) (STYRENE: CEFIC Styrene Distribution Group) 0,49 (butyl acetate = 1) (STYRENE: Occupational health guideline for styrene)*
Flammability (solid, gas)	not applicable
Lower inflammability limit	1,2 Vol% (STYRENE)
Upper inflammability limit	8,9 Vol% (STYRENE)
Lower explosive limit	Not available.
Upper explosive limit	Not available.
Vapour pressure	6,67 hPa (T= 20°C) (STYRENE)
Vapour density	3,6 (air = 1) (STYRENE)

**L7111 - LEVANTE - STUCCO GEL COAT**

Relative density	1.4 g/ml
Solubility	insoluble in water
Partition coefficient: n-octanol/water	2,96 log POW (STYRENE)
Auto-ignition temperature	490°C (1,013 hPa) (STYRENE)
Decomposition temperature	Not available.
Viscosity	50 ± 10 Pas (T=25°C)
Explosive properties	Not applicable.
Oxidising properties	Not applicable.

9.2. Other information

VOC (Directive 2010/75/EC) :	23.55 % - 329.70 g/litre
VOC (volatile carbon) :	21.69 % - 303.67 g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

STYRENE

Polymerises at temperatures above 65°C/149°F. Fire hazard. Possibility of explosion.

Added with an inhibitor that requires a small amount of dissolved oxygen at temperatures < 25°C/77°F.

METHYL ETHYL KETONE

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

1-METHOXY-2-PROPANOL

Dissolves various plastic materials. Stable in normal conditions of use and storage.

Absorbs and dissolves in water and in organic solvents. With air it may slowly form explosive peroxides.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

STYRENE

May react dangerously with: peroxides, strong acids. May polymerise on contact with: aluminium trichloride, azobisisobutyronitrile, dibenzoyl

**L7111 - LEVANTE - STUCCO GEL COAT**

peroxide,sodium.Risk of explosion on contact with: butyllithium,chlorosulphuric acid,diterbutyl peroxide,oxidising substances,oxygen.

METHYL ETHYL KETONE

May form peroxides with: air,light,strong oxidising agents.Risk of explosion on contact with: hydrogen peroxide,nitric acid,sulphuric acid.May react dangerously with: oxidising agents,trichloromethane,alkalis.Forms explosive mixtures with: air.

1-METHOXY-2-PROPANOL

May react dangerously with: strong oxidising agents,strong acids.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

STYRENE

Avoid contact with: oxidising substances,copper,strong acids.

METHYL ETHYL KETONE

Avoid exposure to: sources of heat.

1-METHOXY-2-PROPANOL

Avoid exposure to: air.

10.5. Incompatible materials**STYRENE**

Incompatible materials: plastic materials.

METHYL ETHYL KETONE

Incompatible with: strong oxidants,inorganic acids,ammonia,copper,chloroform.

1-METHOXY-2-PROPANOL

Incompatible with: oxidising substances,strong acids,alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**L7111 - LEVANTE - STUCCO GEL COAT****11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

STYRENE

WORKERS: inhalation; contact with the skin.

1-METHOXY-2-PROPANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

STYRENE

The acute toxicity by inhalation at 1000 ppm affects the central nervous system with headache and dizziness, lack of coordination; irritation of the eye and respiratory tract mucous membranes occurs at 500 ppm. Chronic exposure causes depression of the central and peripheral nervous system with loss of memory, headache and drowsiness starting at 20 ppm; digestive disorders with nausea and loss of appetite; irritation of the respiratory tract with chronic bronchitis; dermatosis. Repeated exposure, at low doses of inhaled substance, causes irreversible changes to hearing and may cause changes in colour vision. No certain data is available on the reversibility of the visual impairment. Repeated skin exposure causes irritation. The substance degreases the skin, which can cause dryness and cracking.

1-METHOXY-2-PROPANOL

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product. Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported.

Interactive effects

STYRENE

The metabolism of the substance is inhibited by ethanol. When styrene is photo-oxidised with ozone and nitrogen dioxide, as in the formation of smog, products highly irritating for the human eye may ensue.

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

> 20 mg/l

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

STYRENE



L7111 - LEVANTE - STUCCO GEL COAT

LD50 (Oral) 5000 mg/kg Rat (MSDS Supplier)

LD50 (Dermal) > 2000 mg/kg Rat (OECD Guideline 402)

LC50 (Inhalation) 11.8 mg/l/4h Rat (Archives of Environmental Health 18: 878-882 - sito ECHA)

1-METHOXY-2-PROPANOL

LD50 (Oral) 4016 mg/kg Rat, equivalent or similar to (EU Method B.1)

LD50 (Dermal) > 2000 mg/kg Rat, equivalent or similar to (EU Method B.3)

LC50 (Inhalation) 54.6 mg/l/4h Rat

METHYL ETHYL KETONE

LD50 (Oral) 2193 mg/kg Rat (read-across from supporting substance, Equivalent or similar to OECD Guideline 423)

LD50 (Dermal) 6480 mg/kg Rabbit (Shell Chemical Company. Vol. MSDS-5390-4)

LC50 (Inhalation) 5000 ppm Rat (Rif. SDS Brenntag)

COBALT BIS 2-ETHYL HEXANOATE

LD50 (Oral) 3129 mg/kg Rat - Sprague-Dawley according to (OECD Guideline 425)

LD50 (Dermal) > 2000 mg/kg Rat - Wistar according to (OECD Guideline 402)

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

**L7111 - LEVANTE - STUCCO GEL COAT**

STYRENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2002).
Classified as "probable carcinogen" by the US National Toxicology Program (NTP) - (US DHHS, 2014).

REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Causes damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: 50 ± 10 Pas (T=25°C)

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

STYRENE

LC50 - for Fish	10 mg/l/96h Pimephales promelas (OECD Guideline 203, GLP)
EC50 - for Crustacea	4.7 mg/l/48h Daphnia magna (OECD Guideline 202, GLP)
EC50 - for Algae / Aquatic Plants	4.9 mg/l/72h Selenastrum capricornutum (EPA OTS 797.1050, GLP)
Chronic NOEC for Crustacea	1.01 mg/l/21d Daphnia magna (OECD Guideline 211, GLP)

1-METHOXY-2-PROPANOL

LC50 - for Fish	> 1000 mg/l/96h Oncorhynchus mykiss, equivalent or similar to (OECD Guideline 203)
EC50 - for Crustacea	> 21100 mg/l/48h Daphnia magna, according to (Test Method No. ESR-ES-15)
EC50 - for Algae / Aquatic Plants	> 1000 mg/l/72h Pseudokirchnerella subcapitata, according to (Test method ET-11-1987-1)

METHYL ETHYL KETONE

LC50 - for Fish	2993 mg/l/96h Pimephales promelas (OECD Guideline 203, GLP)
EC50 - for Crustacea	308 mg/l/48h Daphnia magna (OECD Guideline 202, GLP)
EC50 - for Algae / Aquatic Plants	1972 mg/l/72h Selenastrum capricornutum (OECD Guideline 201, GLP)

**L7111 - LEVANTE - STUCCO GEL COAT****12.2. Persistence and degradability**

STYRENE

Solubility in water 320 mg/l

Rapidly degradable
10 d, 68% according to (ISO DIS 9408)

1-METHOXY-2-PROPANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

METHYL ETHYL KETONE

Solubility in water > 10000 mg/l

Rapidly degradable
(OECD Guideline 301 D, GLP)

COBALT BIS 2-ETHYL HEXANOATE

Solubility in water > 10000 mg/l

Rapidly degradable
approximately 60% CO₂ evolution over a 10 day interval, according to (OECD Guideline 301 B)**12.3. Bioaccumulative potential**

STYRENE

Partition coefficient: n-octanol/water 2.96

BCF 74

1-METHOXY-2-PROPANOL

Partition coefficient: n-octanol/water < 1

METHYL ETHYL KETONE

Partition coefficient: n-octanol/water 0.3

12.4. Mobility in soil

STYRENE

Partition coefficient: soil/water 352 (Section 4.3 of Chapter on QSAR in the TGD)

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

**L7111 - LEVANTE - STUCCO GEL COAT****SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number**

ADR / RID, IMDG, 3269
IATA:

14.2. UN proper shipping name

ADR / RID: POLYESTER RESIN KIT
IMDG: POLYESTER RESIN KIT
IATA: POLYESTER RESIN KIT

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3

**14.4. Packing group**

ADR / RID, IMDG, III
IATA:

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: --

Limited Quantities: 5 L

Tunnel restriction code: (E)

**L7111 - LEVANTE - STUCCO GEL COAT**

Special Provision: -

IMDG:	EMS: F-E, S-D	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 10 Kg	Packaging instructions: 370
	Pass.:	Maximum quantity: 10 Kg	Packaging instructions: 370
	Special Instructions:	A66, A163	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: P5b FLAMMABLE LIQUIDS

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Product

Point

3. Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/ 2008:

- (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;
- (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;
- (c) hazard class 4.1;
- (d) hazard class 5.1.

40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

**L7111 - LEVANTE - STUCCO GEL COAT**

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

STYRENE

METHYL ETHYL KETONE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.

**L7111 - LEVANTE - STUCCO GEL COAT**

H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Use descriptor system:

AC	13	Plastic articles
ERC	2	Formulation into mixture
ERC	6c	Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article)
ERC	6d	Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)
PC	32	Polymer preparations and compounds
PC	9a	Coatings and paints, thinners, paint removers
PROC	1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC	10	Roller application or brushing
PROC	11	Non industrial spraying
PROC	13	Treatment of articles by dipping and pouring
PROC	14	Tabletting, compression, extrusion, pelletisation, granulation
PROC	15	Use as laboratory reagent
PROC	3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC	4	Chemical production where opportunity for exposure arises
PROC	5	Mixing or blending in batch processes
PROC	7	Industrial spraying
PROC	8a	Transfer of substance or mixture (charging and discharging) at non- dedicated facilities
PROC	8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC	9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
SU	10	Formulation [mixing] of preparations and/or re-packaging (excluding alloys)
SU	12	Manufacture of plastics products, including compounding and conversion
SU	17	General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**L7111 - LEVANTE - STUCCO GEL COAT****GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) – Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.
This document must not be regarded as a guarantee on any specific product property.
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.
Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.
The data for evaluation of chemical-physical properties are reported in section 9.

Istituto Superiore di Sanità (ISS) – Archivio Preparati Pericolosi

Codice azienda: IT00465900728
Ragione sociale: Ilpa Adesivi Srl
Nome prodotto ISS: L7111
Codice prodotto ISS: L7111

Training for workers:

Worker training should include content, updates and duration depending on the risk profiles assigned to the business sectors they belong