



ILPA ADESIVI SRL

Revision nr. 2

Dated 14/07/2021

Printed on 14/07/2021

Page n. 1/21

Replaced revision:1 (Printed on: 11/04/2016)

**M8142 - PASTA COLORANTE POLIESTERE**

## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: M8131, M8142, M8143, M8144, M8145, M8146, M8147, M8157, M8165, M8166, M8167  
Product name: PASTA COLORANTE POLIESTERE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Coloring paste unsaturated polyester. Professional use only.

#### Uses related to substances:

Identified Uses	Industrial	Professional	Consumer
2-METHOXY-1-METHYLETHYL ACETATE	-	ERC: 8a, 8c, 8d. PROC: 1, 10, 11, 13, 15, 19, 2, 3, 4, 5, 8a, 8b, 9.	-

Uses advised against: no one in particular

#### 1.3. Details of the supplier of the safety data sheet

Name: ILPA ADESIVI SRL  
Full address: Via Ferorelli, 4  
District and Country: 70132 BARI (BARI)  
ITALIA  
Tel. + 39 0805383837  
Fax + 39 0805377807

e-mail address of the competent person responsible for the Safety Data Sheet: laboratorio@ilpa.it

#### 1.4. Emergency telephone number

For urgent inquiries refer to: + 39 0808974667 (Technical support - 8,00 - 17,00 - LUN-VEN; MON-FRI)(Italian time zone)  
Safety Executive (HSE) Chemicals Regulation Directorate 5S.1 Redgrave Court, Merton Road, Bootle, Merseyside. L20 7HS.  
Phone: +44 151 9513317

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture



The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

**Hazard classification and indication:**

Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.

**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

**Hazard pictograms:**

Signal words: Warning

**Hazard statements:**

<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H317</b>	May cause an allergic skin reaction.

**Precautionary statements:**

<b>P280</b>	Wear protective gloves / eye protection / face protection.
<b>P333+P313</b>	If skin irritation or rash occurs: Get medical advice / attention.
<b>P337+P313</b>	If eye irritation persists: Get medical advice / attention.
<b>P362+P364</b>	Take off contaminated clothing and wash it before reuse.

**Contains:** 2-hydroxyethyl methacrylate  
MALEIC ANHYDRIDE

Product not intended for uses provided for by Dir. 2004/42/CE.

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

**M8142 - PASTA COLORANTE POLIESTERE**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>2-hydroxyethyl methacrylate</b>		
CAS 868-77-9	$25,5 \leq x < 27$	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Classification note/notes according to Annex VI to the CLP Regulation: D
EC 212-782-2		
INDEX 607-124-00-X		
Reg. no. 01-2119490169-29		
<b>ACETONE</b>		
CAS 67-64-1	$1,5 \leq x < 2$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 200-662-2		
INDEX 606-001-00-8		
Reg. no. 01-2119471330-49		
<b>STYRENE</b>		
CAS 100-42-5	$0,7 \leq x < 0,8$	Flam. Liq. 3 H226, Repr. 2 H361d, Acute Tox. 4 H332, STOT RE 1 H372, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note/notes according to Annex VI to the CLP Regulation: D
EC 202-851-5		
INDEX 601-026-00-0		
Reg. no. 01-2119457861-32		
<b>MALEIC ANHYDRIDE</b>		
CAS 108-31-6	$0,001 \leq x < 0,05$	Acute Tox. 4 H302, STOT RE 1 H372, Skin Corr. 1B H314, Eye Dam. 1 H318, Resp. Sens. 1 H334, Skin Sens. 1A H317, EUH071
EC 203-571-6		
INDEX 607-096-00-9		
Reg. no. 01-2119472428-31-XXXX		
<b>DIPROPYLENE GLYCOL MONOMETHYL ETHER</b>		
CAS 34590-94-8	$0 \leq x < 0,05$	Substance with a community workplace exposure limit.
EC 252-104-2		
INDEX -		
Reg. no. 01-2119450011-60-XXXX		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

**M8142 - PASTA COLORANTE POLIESTERE**

PROTECTIVE MEASURES FOR THE FIRST RESCUE WORKERS: for PPE (personal protection equipment) required for first aid refer to section 8.2 of this safety data sheet.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

**M8142 - PASTA COLORANTE POLIESTERE**

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s)**

No use other than specified in Section 1.2 of this safety data sheet.

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2019
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξινόγους παράγοντες κατά την εργασία``»
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemičkim na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
ROU	România	Hotararea 157/2020 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici, precum și pentru modificarea și completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția lucrătorilor împotriva riscurilor legate de expunerea la agenți cancerigeni sau mutageni la locul de muncă
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive

**M8142 - PASTA COLORANTE POLIESTERE**

TLV-ACGIH

2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.  
ACGIH 2020**2-hydroxyethyl methacrylate**

## Predicted no-effect concentration - PNEC

Normal value in fresh water	0,482	mg/l
Normal value in marine water	0,482	mg/l
Normal value for fresh water sediment	3,79	mg/kg/d
Normal value for marine water sediment	3,79	mg/kg/d
Normal value for water, intermittent release	1	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,476	mg/kg/d

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			NPI	0,83 mg/kg bw/d				
Inhalation	NPI	NPI	NPI	2,9 mg/m3	NPI	NPI	NPI	4,9 mg/m3
Skin	NPI	NPI	NPI	0,83 mg/kg bw/d	NPI	NPI	NPI	1,3 mg/kg bw/d

**ACETONE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1200	500	2400 (C)	1000 (C)	
MAK	DEU	1200	500	2400	1000	
VLEP	FRA	1210	500	2420	1000	
TLV	GRC	1780		3560		
GVI/KGVI	HRV	1210	500			
VLEP	ITA	1210	500			
TGG	NLD	1210		2420		
VLE	PRT	1210	500			
TLV	ROU	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	

## Predicted no-effect concentration - PNEC

Normal value in fresh water	10,6	mg/l
Normal value in marine water	1,06	mg/l
Normal value for fresh water sediment	30,4	mg/kg/d
Normal value for marine water sediment	3,04	mg/kg/d
Normal value for water, intermittent release	21	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	29,5	mg/kg/d

**M8142 - PASTA COLORANTE POLIESTERE****Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	62 mg/kg bw/d				
Inhalation			VND	200 mg/m3	2420 mg/m3	VND	VND	1210 mg/m3
Skin			VND	62 mg/kg bw/d			VND	186 mg/kg bw/d

**STYRENE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	86	20	172	40	
VLA	ESP	86	20	172	40	
VLEP	FRA	100	23,3	200	46,6	
TLV	GRC	425	100	1050	250	
GVI/KGVI	HRV	430	100	1080	250	SKIN
TGG	NLD	107				
TLV	ROU	50	12	150	35	
WEL	GBR	430	100	1080	250	
TLV-ACGIH		10		20		

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,028	mg/l
Normal value in marine water	0,014	mg/l
Normal value for fresh water sediment	0,614	mg/kg/d
Normal value for marine water sediment	0,0614	mg/kg/d
Normal value for water, intermittent release	0,04	mg/l
Normal value of STP microorganisms	5	mg/l
Normal value for the terrestrial compartment	0,2	mg/kg/d

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	2,1 mg/kg bw/d				
Inhalation	182,75 mg/m3	174,25 mg/m3	VND	10,2 mg/m3	306 mg/m3	289 mg/m3	VND	85 mg/m3
Skin			VND	343 mg/kg bw/d			VND	406 mg/kg bw/d

**MALEIC ANHYDRIDE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	0,081	0,02	0,081 (C)	0,02 (C)	
MAK	DEU	0,081	0,02	0,081 (C)	0,02 (C)	C = 0,20 mg/m3
VLA	ESP	0,4	0,1			

**ILPA ADESIVI SRL**

Revision nr. 2

Dated 14/07/2021

Printed on 14/07/2021

Page n. 8/21

Replaced revision:1 (Printed on: 11/04/2016)

**M8142 - PASTA COLORANTE POLIESTERE**

VLEP	FRA	1				
TLV	GRC	1				
GVI/KGVI	HRV	0,41	0,1	0,8	0,2	INHAL
GVI/KGVI	HRV	0,41	0,1	0,8	0,2	SKIN
TLV	ROU	1	0,25	3	0,75	
WEL	GBR	1		3		
TLV-ACGIH		0,01	0,0025			

Predicted no-effect concentration - PNEC		
Normal value in fresh water		0,075 mg/l
Normal value in marine water		0,0075 mg/l
Normal value for fresh water sediment		0,06 mg/kg
Normal value for marine water sediment		0,006 mg/kg
Normal value for water, intermittent release		48,1 mg/l
Normal value of STP microorganisms		4,46 mg/l
Normal value for the food chain (secondary poisoning)		6,67 mg/kg
Normal value for the terrestrial compartment		0,01 mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		0,1 mg/kg bw/d		0,06 mg/kg bw/d				
Inhalation			0,08 mg/m3	0,05 mg/m3	0,8 mg/m3	0,8 mg/m3	0,32 mg/m3	0,19 mg/m3
Skin		0,1 mg/kg bw/d		0,1 mg/kg bw/d		0,2 mg/kg bw/d		0,2 mg/kg bw/d

DIPROPYLENE GLYCOL MONOMETHYL ETHER						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	310	50	310	50	
MAK	DEU	310	50	310	50	
VLA	ESP	308	50			SKIN
VLEP	FRA	308	50			SKIN
TLV	GRC	600	100	900	150	
GVI/KGVI	HRV	308	50			SKIN
VLEP	ITA	308	50			SKIN
TGG	NLD	300				
VLE	PRT	308	50			SKIN
TLV	ROU	308	50			SKIN
WEL	GBR	308	50			SKIN
OEL	EU	308	50			SKIN
TLV-ACGIH		606	100	909	150	SKIN
Predicted no-effect concentration - PNEC						





**M8142 - PASTA COLORANTE POLIESTERE**

Normal value in fresh water	19	mg/l
Normal value in marine water	1,9	mg/l
Normal value for fresh water sediment	70,2	mg/kg
Normal value for marine water sediment	7,02	mg/kg
Normal value for water, intermittent release	190	mg/l
Normal value of STP microorganisms	4168	mg/l
Normal value for the terrestrial compartment	2,74	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1,67 mg/kg bw/d				
Inhalation				37,2 mg/m3				310 mg/m3
Skin				15 mg/kg bw/d				65 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**M8142 - PASTA COLORANTE POLIESTERE****ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	pasty liquid	
Colour	various	
Odour	mild	
Odour threshold	Not available	
pH	Not applicable	
Melting point / freezing point	Not available	Substance:2-hydroxyethyl methacrylate Temperature:<-60°C
Initial boiling point	Not available	Substance:2-hydroxyethyl methacrylate Temperature:213°C (101,3 kPa)
Boiling range	Not available	
Flash point	> 60 °C	
Evaporation rate	Not available	
Flammability (solid, gas)	not applicable	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	Concentration:8 Pa (T=20°C) Substance:2-hydroxyethyl methacrylate
Vapour density	Not available	Concentration:4,5 (air=1) Substance:2-hydroxyethyl methacrylate
Relative density	1,9 g/ml	
Solubility	Not available	Concentration:≥100g/l (T=20°C) Substance:2-hydroxyethyl methacrylate
Partition coefficient: n-octanol/water	Not available	Concentration:Log Pow 0,42 (T=20°C) Substance:2-hydroxyethyl methacrylate
Auto-ignition temperature	Not available	Substance:2-hydroxyethyl methacrylate Temperature:375°C (1 Bar)
Decomposition temperature	Not available	
Viscosity	2000 ± 500 Pas (T = 25 °C)	
Explosive properties	Product does not present an explosion hazard.	Substance:2-hydroxyethyl methacrylate
Oxidising properties	not applicable	

**9.2. Other information**

VOC (Directive 2010/75/EC) :	2,30 % - 43,72 g/litre
VOC (volatile carbon) :	1,67 % - 31,66 g/litre



## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### ACETONE

Decomposes under the effect of heat.

#### STYRENE

Polymerises at temperatures above 65°C/149°F. Fire hazard. Possibility of explosion.

Added with an inhibitor that requires a small amount of dissolved oxygen at temperatures < 25°C/77°F.

#### DIPROPYLENE GLYCOL MONOMETHYL ETHER

Forms peroxides with: air.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

#### ACETONE

Risk of explosion on contact with: bromine trifluoride, fluorine dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxymonosulphuric acid, phosphoryl oxychloride, chromosulphuric acid, fluorine, strong oxidising agents, strong reducing agents. Develops flammable gas on contact with: nitrosyl perchlorate.

#### STYRENE

May react dangerously with: peroxides, strong acids. May polymerise on contact with: aluminium trichloride, azobisisobutyronitrile, dibenzoyl peroxide, sodium. Risk of explosion on contact with: butyllithium, chlorosulphuric acid, diterbutyl peroxide, oxidising substances, oxygen.

#### DIPROPYLENE GLYCOL MONOMETHYL ETHER

May react violently with: strong oxidising agents.

### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

#### ACETONE

Avoid exposure to: sources of heat, naked flames.

**M8142 - PASTA COLORANTE POLIESTERE**

## STYRENE

Avoid contact with: oxidising substances,copper,strong acids.

## DIPROPYLENE GLYCOL MONOMETHYL ETHER

Avoid exposure to: sources of heat.Possibility of explosion.

**10.5. Incompatible materials**

## ACETONE

Incompatible with: acids,oxidising substances.

## STYRENE

Incompatible materials: plastic materials.

**10.6. Hazardous decomposition products**

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## ACETONE

May develop: ketenes,irritant substances.

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

## STYRENE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

## STYRENE

The acute toxicity by inhalation at 1000 ppm affects the central nervous system with headache and dizziness, lack of coordination; irritation of the eye



and respiratory tract mucous membranes occurs at 500 ppm. Chronic exposure causes depression of the central and peripheral nervous system with loss of memory, headache and drowsiness starting at 20 ppm; digestive disorders with nausea and loss of appetite; irritation of the respiratory tract with chronic bronchitis; dermatosis. Repeated exposure, at low doses of inhaled substance, causes irreversible changes to hearing and may cause changes in colour vision. No certain data is available on the reversibility of the visual impairment. Repeated skin exposure causes irritation. The substance degrades the skin, which can cause dryness and cracking.

#### Interactive effects

#### STYRENE

The metabolism of the substance is inhibited by ethanol. When styrene is photo-oxidised with ozone and nitrogen dioxide, as in the formation of smog, products highly irritating for the human eye may ensue.

#### ACUTE TOXICITY

ATE (Inhalation) of the mixture:  
Not classified (no significant component)  
ATE (Oral) of the mixture:  
Not classified (no significant component)  
ATE (Dermal) of the mixture:  
Not classified (no significant component)

#### 2-hydroxyethyl methacrylate

LD50 (Oral) 5564 mg/kg RAT, according to (FDA, 1959 in food, drugs and cosmetics)

LD50 (Dermal) > 5000 mg/kg RABBIT, (standard acute method)

#### DIPROPYLENE GLYCOL MONOMETHYL ETHER

LD50 (Oral) > 5000 mg/kg RAT

LD50 (Dermal) > 9500 mg/kg RAT

#### STYRENE

LD50 (Oral) 5000 mg/kg Rat (MSDS Supplier)

LD50 (Dermal) > 2000 mg/kg Rat (OECD Guideline 402)

LC50 (Inhalation) 11,8 mg/l/4h Rat (Archives of Environmental Health 18: 878-882 - sito ECHA)

#### ACETONE

LD50 (Oral) 5800 mg/kg rat, (standard acute method)

#### MALEIC ANHYDRIDE



LD50 (Oral) 400 mg/kg Rat

LD50 (Dermal) 610 mg/kg Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

STYRENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2002).  
Classified as "probable carcinogen" by the US National Toxicology Program (NTP) - (US DHHS, 2014).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: 2000 ± 500 Pas (T = 25 °C)

## SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**M8142 - PASTA COLORANTE POLIESTERE****12.1. Toxicity**

## 2-hydroxyethyl methacrylate

LC50 - for Fish	> 100 mg/l/96h <i>Oryzias latipes</i> , according to (OECD Guideline 203)
EC50 - for Crustacea	380 mg/l/48h <i>Daphnia magna</i> , according to (OECD Guideline 202)
EC50 - for Algae / Aquatic Plants	345 mg/l/72h <i>Selenastrum capricornutum</i> , according to (OECD Guideline 201)
Chronic NOEC for Crustacea	24,1 mg/l 21 d <i>Daphnia magna</i> (OECD Guideline 211 (Daphnia magna Reproduction Test))

## STYRENE

LC50 - for Fish	10 mg/l/96h <i>Pimephales promelas</i> (OECD Guideline 203, GLP)
EC50 - for Crustacea	4,7 mg/l/48h <i>Daphnia magna</i> (OECD Guideline 202, GLP)
EC50 - for Algae / Aquatic Plants	4,9 mg/l/72h <i>Selenastrum capricornutum</i> (EPA OTS 797.1050, GLP)
Chronic NOEC for Crustacea	1,01 mg/l/21d <i>Daphnia magna</i> (OECD Guideline 211, GLP)

## ACETONE

LC50 - for Fish	5540 mg/l/96h <i>Oncorhynchus mykiss</i> , according to (Aquatic Organisms (US EPA) 1975)
EC50 - for Crustacea	8800 mg/l/48h <i>Daphnia pulex</i> , (Adema, D.M.M. (1978) <i>Hydrobiologia</i> 59, 125-134)
Chronic NOEC for Crustacea	2212 mg/l <i>Daphnia magna</i> , 28d according to OECD 211 with deviations

**12.2. Persistence and degradability**

## 2-hydroxyethyl methacrylate

Rapidly degradable  
92-100% after 14 days, according to (OECD Guideline 301 C)

DIPROPYLENE GLYCOL MONOMETHYL  
ETHER

Solubility in water 1000 - 10000 mg/l  
Rapidly degradable

## STYRENE

Solubility in water 320 mg/l  
Rapidly degradable  
10 d, 68% according to (ISO DIS 9408 )

## ACETONE

Rapidly degradable

## MALEIC ANHYDRIDE

Solubility in water > 10000 mg/l  
Entirely degradable

**12.3. Bioaccumulative potential**

**M8142 - PASTA COLORANTE POLIESTERE**

2-hydroxyethyl methacrylate

Partition coefficient: n-octanol/water

0,42 Log Kow (OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)).

DIPROPYLENE GLYCOL MONOMETHYL  
ETHER

Partition coefficient: n-octanol/water

0,0043

STYRENE

Partition coefficient: n-octanol/water

2,96

BCF

74

ACETONE

Partition coefficient: n-octanol/water

-0,23

BCF

3

MALEIC ANHYDRIDE

Partition coefficient: n-octanol/water

-2,78

**12.4. Mobility in soil**

STYRENE

Partition coefficient: soil/water

352 (Section 4.3 of Chapter on QSAR in the TGD)

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of





ILPA ADESIVI SRL

Revision nr. 2

Dated 14/07/2021

Printed on 14/07/2021

Page n. 17/21

Replaced revision:1 (Printed on: 11/04/2016)

**M8142 - PASTA COLORANTE POLIESTERE**

the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

**14.1. UN number**

Not applicable

**14.2. UN proper shipping name**

Not applicable

**14.3. Transport hazard class(es)**

Not applicable

**14.4. Packing group**

Not applicable

**14.5. Environmental hazards**

Not applicable

**14.6. Special precautions for user**

Not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**SECTION 15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

**M8142 - PASTA COLORANTE POLIESTERE**Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Product

Point 3. Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/ 2008:  
(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;  
(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;  
(c) hazard class 4.1;  
(d) hazard class 5.1.  
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.

Contained substance

Point	75	2-hydroxyethyl methacrylate Reg. no.: 01-2119490169-29
Point	75	STYRENE Reg. no.: 01-2119457861-32
Point	75	MALEIC ANHYDRIDE Reg. no.: 01-2119472428-31-XXXX

Regulation (EC) No. 2019/1148 - on the marketing and use of explosives precursorsRegulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

**M8142 - PASTA COLORANTE POLIESTERE**

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**15.2. Chemical safety assessment**

A chemical safety assessment has been performed for the following contained substances

STYRENE

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Repr. 2</b>	Reproductive toxicity, category 2
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>STOT RE 1</b>	Specific target organ toxicity - repeated exposure, category 1
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Resp. Sens. 1</b>	Respiratory sensitization, category 1
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Skin Sens. 1A</b>	Skin sensitization, category 1A
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H302</b>	Harmful if swallowed.
<b>H332</b>	Harmful if inhaled.
<b>H372</b>	Causes damage to organs through prolonged or repeated exposure.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H334</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled.



## M8142 - PASTA COLORANTE POLIESTERE

H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

## Use descriptor system:

ERC	8a	Widespread use of non- reactive processing aid (no inclusion into or onto article, indoor)
ERC	8c	Widespread use leading to inclusion into/onto article (indoor)
ERC	8d	Widespread use of non- reactive processing aid (no inclusion into or onto article, outdoor)
PROC	1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC	10	Roller application or brushing
PROC	11	Non industrial spraying
PROC	13	Treatment of articles by dipping and pouring
PROC	15	Use as laboratory reagent
PROC	19	Manual activities involving hand contact
PROC	2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC	3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC	4	Chemical production where opportunity for exposure arises
PROC	5	Mixing or blending in batch processes
PROC	8a	Transfer of substance or mixture (charging and discharging) at non- dedicated facilities
PROC	8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC	9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

## LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**M8142 - PASTA COLORANTE POLIESTERE****GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
  16. Regulation (EU) 2019/521 (XII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Regulation (EU) 2020/217 (XIV Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) – Italy

**Istituto Superiore di Sanità (ISS) – Archivio Preparati Pericolosi**

Codice azienda: IT00465900728

Ragione sociale: Ilpa Adesivi Srl

Nome prodotto ISS: M8142

Codice prodotto ISS: M8142

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

**Training for workers:**

Worker training should include content, updates and duration depending on the risk profiles assigned to the business sectors they belong

**Changes to previous review:**

The following sections were modified:

01 / 02 / 03 / 04 / 05 / 07 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.