



a d e s i v i

TECHNICAL DATA SHEET



Review 003, 05/2016

Page 1 of 2

PRODUCT

RENOVATOR TEAK - Whitener and stain remover for fine woods (L7104)

FEATURES

The precious woods such as teak, exposed to salt, to the sun, have the risk to darken and to lose their charm.

LEVANTE RENOVATOR TEAK based on acids and surfactants, gives a deep cleaning, removes stains and whitens any wooden surface, bringing back the essence to its original splendor.

Renovator Teak is efficient, but delicate. It cleans without damaging the oily nature and restoring the natural color of the wood.

TECHNICAL DATA

| | | |
|-----------------|------------------------|----------|
| Specific weight | 1150 ± 10 g/l | (MI 001) |
| Color | Colorless, transparent | |

STORAGE

Keep the container well closed and stored in a cool (temperature below 25°C) and ventilated environment for a maximum period of 12 months from the date of production marked on the tin. Avoid direct sun exposure.

SAFETY

During application and drying time ventilate the room. We recommend the use of appropriate PPE during application. Before starting work, read the safety card carefully.

APPLICATION

- Apply LEVANTE RENOVATOR TEAK as it is or diluted with water;
- Spread LEVANTE RENOVATOR TEAK and rub the surface or with a stiff latex sponge or with a hard bristle brush;
- Repeat the operation until the dirt is completely removed, wash thoroughly with water and let it dry completely;
- Apply LEVANTE TEAK OIL.

ILPA ADESIVI SRL

TECHNICAL DATA SHEET




Review 003, 05/2016

Page 2 of 2




Application

Sponge or brush



Dilution

With water from 1:1 to 1:10



Theoretical yield

10 m²/l

(MI 014)

OTHER INFORMATION

Worn wooden surface should be treated before with LEVANTE RENOVATOR TEAK and then with LEVANTE TEAK OIL in order to come back as new.

