

# TECHNICAL DATA SHEET

Review 004, 05/2016

Page 1 of 2



## PRODUCT

ULTRAPOLISH (L7107)

## FEATURES

ULTRAPOLISH is composed by selected waxes and metal oxides to achieve maximum results with minimum effort. It is liquid and easy to apply even for inexperienced users.

ULTRAPOLISH is characterized by an excellent abrasive power through the mix of metal oxides, indeed it easily removes scratches, coats of old varnishes, old and yellowish gelcoat, restoring the treated surface as new with high gloss.

## DATI TECNICI

Specific weight	1400 ± 20 g/l	(MI 001)
Solids by weight	68%	(MI 006)
Color	Ice white	
Theoretical yield	6-10 g/m <sup>2</sup>	(MI 014)

## STORAGE

Keep the container well closed and stored in a cool (temperature below 25°C) and ventilated environment for a maximum period of 12 months from the date of production marked on the tin. Avoid direct sun exposure.

## SAFETY RULES

During the application and the drying time air out the place. It is recommended to use the appropriate PPE during the application phase. Read carefully the safety data sheet before application.

## APPLICAZIONE

- Be sure that the surfaces to be treated are dry and clean;
- Shake the container to get a homogeneous cream;
- Apply the right amount of ULTRAPOLISH directly on the surface to be treated (for a 50x50 cm<sup>2</sup> surface, use 3-5 g of product) distributing it on uniformly;
- Polishing using an angle grinder or a polisher with adjustable speed by applying low pressure and using a medium-low speed (2000 - 2500 rpm). Repeat the treatment if it is necessary;
- Eliminate the excess with a clean cloth.

# TECHNICAL DATA SHEET

Review 004, 05/2016

Page 2 of 2

