



a d e s i v i

TECHNICAL DATA SHEET



Review 003, 05/2016

Page 1 of 1

PRODUCT

MAX SEALANT BY BRUSH M123 (C7110)

FEATURES

MAX SEALANT BY BRUSH is a product based on synthetic resins and it has a high solid content (HS) and an excellent elasticity. It is thixotropic and ideal for all kind of metal sheets, but it can be used on cement, wood and other synthetic materials too.

MAX SEALANT BY BRUSH can be perfectly re-varnished without any absorption of varnish, its formulation is studied for a fast hardening at contact to air or better in an oven.

Its specific application is for the sealing of bonnet, mudguard, grill, etc.

TECHNICAL DATA

Specific weight	1200 ± 20 g/l	(MI 001)
Solids in weight	69 ± 2 %	(MI 006)
Color	Dark grey	

STORAGE

Keep the container well closed and stored in a cool (temperature below 25°C) and ventilated environment for a maximum period of 12 months from the date of production marked on the tin. Avoid direct sun exposure.

SAFETY

During application and drying time ventilate the room. We recommend the use of appropriate PPE during application. Before starting work, read safety instructions.

APPLICATION

The product can be applied with a normal bristle brush, do not apply if the temperature is lower than 0° C or higher than 40° C. When you got the necessary from the package, re-close promptly, because the contact with the air gets a fast hardening.

ILPA ADESIVI SRL