

# TECHNICAL DATA SHEET



Review 001, 09/2020

Page 1 of 1

## PRODUCT

VELVET ABRASIVE PASTE polishing (C7145)

## FEATURES

VELVET ABRASIVE PASTE polishing is formulated using synthetic waxes and metal oxides. It is characterized by a slight abrasive action, thus it is excellent to remove small scratches and stains from all types of bodywork paints even if oxidated. It does not contain silicones. It can also be used on boats and fiberglass products.

It is ideal to remove the paintings opacity or for car finishing before delivery; its use is very easy with excellent results, thanks to its creaminess.

## TECHNICAL DATA SHEET

	Emulsion based	
Specific weight	1300 ± 20 g/l	(MI 001)
Aspect	Homogeneous paste	
Colour	Black	

## STORAGE

Keep the container well closed and stored in a cool (temperature below 25°C) and ventilated environment for a maximum period of 12 months from the date of production marked on the tin. Avoid direct sun exposure.

## SAFETY RULES

Keep the room ventilated during application and drying processes. During application, the use of personal protective equipment is recommended. Read carefully the safety data sheet before application.

## APPLICATION

- Make sure that the surfaces to be treated are completely dry and clean.
- Apply VELVET ABRASIVE PASTE directly onto the surface to be treated.
- Use it with a polishing sponge and an orbital polisher at variable speed by adopting a medium speed.
- Refinish the previously treated surface using a wool disk.
- The mixture of solvents confers an adequate drying speed that makes its use easier and permits an immediate polish; at the same time, it is possible to polish large areas without running the risk it becomes difficult to remove.

## ADDITIONAL INFORMATION

*Note: In case of excessive thickening add water and mix carefully.*

*Processing should not take place under the direct sun exposure.*